

PRODUCT LINE

Surface Wellhead | Drilling
Wellheads

PRODUCT

G-25 Stacker Drill-Thru System
with Ringlok Latch Technology



Streamline your operations with efficient drilling, casing, and cementing—all without breaking the BOP stack. Built for performance, precision, and adaptability.

The G-25 Stacker Drill-Thru System with Ringlok Latch Technology saves you time by facilitating drilling, running, and cementing intermediate and production casing, while eliminating the need to break the BOP Stack to install an intermediate casing spool. The G-25 Split multi-bowl design provides the flexibility to break connections for contingency plans. Utilizing Innovex Ringlok latch technology eliminates the leak paths associated with conventional lock screws, decreasing confined space work in the cellar and promoting safe handling, as well as reducing HSE exposure.

Options

- BOP Quick Connect Adaptor available for batch drilling operations.
- Land production casing in a fluted mandrel hanger, solid mandrel hanger, or casing slips.
- Available for 2, 3, and 4 string casing programs.
- Bottom Prep available with Slip-on weld, threaded box bottom, or Slip-Lock connections.
- Option to land production casing or tie-back in a nested bowl.
- Contingency casing slips and pack-off assembly provided when casing won't go to the bottom.
- Break the spool connection to access internals for setting contingency casing slips.
- Ability to run control/instrumentation lines within the system upon request.

Specifications

- Available Sizes: 11" and 13"
- Pressure Rating Range: 3000 PSI - 10,000 PSI
- Temperature Range: L (-50) - U (+250)
- Trim Levels: AA to EE
- PSL Ratings: 1, 2, and 3
- Hanger Threads: Standard and Premium Threading available

