

The **BACH™ Production Casing Cement Head** improves operational safety and reliability when launching cement plugs during production casing cementing and/or pressure testing operations. The same head works for 5.00, 5-1/2 and 6.00 inch production casing (at surface).



FEATURES AND BENEFITS

SPEED LOK™ connection, a quick connect adapter that eliminates threading or hammering – easy 360° orientation.

Plug-and-play configuration.

Integral manifold enables simple quarter-turn functionality and keeps the center of gravity close to the centerline for easier and safer lifting.

Mechanical plug launch indicator below the FOSV.

Releasing plunger rods do not extrude when launching cement plugs.

Non welded assembly allows for improved maintenance to be performed to ensure extend the service life of the head.

SPECIFICATIONS

Max Working Pressure¹: **12,000 psi**

Plug Container ID: **6.00 in**

Minimum ID for Plug: **5.38 in**

Bottom Plug Length² (Max.): **26.00 in**

Top Plug Length (Max.)²: **34.44 in**

Overall Length: **170.17 in**

Overall Length: **2,805 lbs.**

¹MAWP is the maximum allowable working pressure to be applied to the BACH during pumping operations. Each BACH is pressure tested to a MATP that is 1.5 x MAWP

²Allowable plug length can be customized to accept extended length plugs common to tapered string and production strings that incorporate restricted ID sleeves