

Innovex's in-house engineered **EZ Dinghy™ Dart Launcher** cement head is the fastest and safest way to launch cementing darts/plugs and foam/solid balls. A simpler, faster, and safer alternative to circulating iron manifolds. The EZ DINGHY™ Dart Launcher features a quick-casing-connect adapter to adapt to the drill pipe, tubing, or casing being used. A super double compact dinghy that is super EZ to use.



FEATURES AND BENEFITS

Available in single and double configurations.

Easy plug launch with a single valve 90-degree rotation.

Optional plug launch indicator.

Ideal for DWC operations where a quick transition from casing running to cementing is required.

SPECIFICATIONS

Max Working Pressure: **10,000 psi**

Max Chamber Length: **20.00 in**

Tensile Capacity: **350 tons**

Main Bore Flow Area¹: **22.15 in²**

Bypass Flow Area¹: **3.14 in²**

Max Main Bore Flow Rate¹: **16 bbl/min**

Max Bypass Flow Rate¹: **8 bbl/min**

Main Bore ID: **5.31 in**

Bypass Bore ID: **2.00 in**

Overall Length: **183.1 in**

Overall Weight: **2,448 lbs**

¹Flow area/rate may be reduced depending on lower adapter

²When configured with elevator lift sub